



主要技术特性要求：

1.使用温度范围：

环境温度：-25 ~ +70℃

相对湿度：95%(40℃)

2.额定负荷：2A 100V AC

3.接触电阻：≤ 30mΩ

4.绝缘电阻：≥ 100MΩ

5.耐 压：500V AC (50Hz) 1min

6.插 拔 力：15 ~ 60N

7.寿 命：≥ 5000次

2	插 针	2	黄铜 Y=0.6mm	D, Ni/Sn
1	基 座	1	PBT	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



<i>Title</i>		Mini Din Jack				
<i>Tolerances</i>	<i>Drawer</i>	<i>Naomi</i>	<i>Part No:</i>			
<i>Linear</i>	<i>Checked</i>	<i>Summer</i>	WCT-DS-2-02BM			
X ±0.15	<i>Approved</i>	<i>Macus</i>	<i>Cus. Part No:</i>			
.X ±0.05	<i>Date</i>	2017.06.27	WCT-DS-2-02BM			
<i>Angles</i>	<i>Projection</i>	<i>Version</i>	<i>Size</i>	<i>A4</i>	<i>Units</i>	
± 3°		A	<i>Scale</i>	1:1	<i>Sheet</i> 1/1	