



PCB板安装孔图

主要技术特性要求：

1.使用温度范围：

环境温度：-25 ~ +70℃

相对湿度：95%(40℃)

2.额定负荷：2A 100V AC

3.接触电阻：≤30mΩ

4.绝缘电阻：≥100MΩ

5.耐压：500V AC (50Hz) 1min

6.插拔力：10 ~ 50N

7.寿命：≥5000次

7	右长针	1	H62黄铜带 Y=0.6mm	D. Cu/Sn
6	左长针	1	H62黄铜带 Y=0.6mm	D. Cu/Sn
5	右短针	1	H62黄铜带 Y=0.6mm	D. Cu/Sn
4	左短针	1	H62黄铜带 Y=0.6mm	D. Cu/Sn
3	接地针	1	黄铜带 Y=0.28mm	D. Cu/Sn
2	后盖	1	PBT	
1	底座	1	PBT	
NO.	DESCRIPTION	QTY	MATERIAL	PLATING



Title		Mini Din Jack			
Tolerances	Drawer	Naomi	Part No:		
	Checked	Summer	WCT-DS-4-03		
Linear	Approved	Macus	Cus. Part No:		
	Date	2017.06.27	WCT-DS-4-03		
Angles	Projection	Version	Size	A4	Units
± 3°		A	Scale	1:1	Sheet 1/1